



Memory Card Choice of Professionals

microSDXC™ Dual-Slot USB 3.1, Gen. 2 Workflow Reader

USB 3.1, Gen. 2 Transfer Speed

Transfer your data files at speeds of up to 10Gb/s (1.25GB/s) using the ProGrade Digital microSDXC™ Dual-Slot Workflow Reader. Indispensable for drone, action cam, video and photography workflows where large volumes of data files are the norm, this reader provides simultaneous rapid and efficient transfer of data from cards in both slots.

Portable and compact, the ProGrade Digital microSDXC Dual-Slot reader features an industry-first magnetic base that pairs to an included metal plate. Affix the small metal plate to laptop or host device, then connect the reader to safely and efficiently transfer files—whether working in the field or studio. Two included 18" USB connector cables ensure device interoperability. Features LED indicator to show data transfer activity.

The ProGrade Digital microSDXC Dual-Slot reader is backwards compatible with USB 3.0 host devices, and supports microSDXC cards. For use with Mac™ OS X 10.6 or later and Windows™ 10 operating systems. This reader takes advantage of the latest generation USB 3.1, Gen. 2 interface, which is up to two times faster than USB 3.0.

ProGrade Digital microSDXC Dual-Slot USB 3.1, Gen. 2 Reader Key Features:

- Dual-slot reader for microSDXC cards
- Data transfer speed of up to 10Gb/s (1.25GB/s)
- Supports simultaneous maximum speed transfer of data from cards in both slots
- USB 3.1, Gen. 2 interface
- LED indicator for data transfer activity
- Portable and compact
- Includes two 18" connection cables: one Type A to Type C and one Type C to Type C
- Magnetized reader bottom connects reader to laptop (using included metal mounting plate)
- Compatible with Mac OS X 10.6 or later and Windows 10
- Backwards compatible with USB 3.0 devices
- Dimensions: 70.8 mm x 70.8 mm x 18 mm
- 2-year warranty



www.progradedigital.com



1GB=1,000,000,000 bytes. Actual user storage is less. Speed is based on internal testing; user's performance may be lower depending on host device, interface, usage conditions and other factors. 1MB = 1,000,000 bytes.

©2018 ProGrade Digital, Inc. All rights reserved. Information, products, and/or specifications are subject to change without notice. ProGrade Digital, Inc. is not responsible for omissions or errors in typography or photography. ProGrade and the ProGrade Logo are trademarks of ProGrade Digital Inc. ProGrade Digital is an authorized licensee of SDXC, microSDXC, CFast 2.0, CompactFlash, and CFexpress trademarks. All other brand or product names in the release are trademarks or registered trademarks of their respective holders. See product packaging and www.progradedigital.com for additional information and limitations. ProGrade Digital memory cards and card readers are available for purchase online at ProGradeDigital.com, plus the company's Amazon and B&H Photo and Video websites.

ProGradeDigital 1660 Hamilton Ave. Suite 101, San Jose, CA 95125, USA

PS-PG-07-09-23-18