

CompactFlash™ & SD™ Dual-Slot USB 3.2, Gen. 2 Workflow Reader

USB 3.2, Gen. 2 Transfer Speed

Transfer your data files at speeds of up to 10Gb/s (1.25GB/s) using the ProGrade Digital CompactFlash™ & SD™ Dual-Slot Workflow Reader. Indispensable for cinema, video and photography workflows where large volumes of data files are the norm, this reader provides simultaneous rapid and efficient transfer of data from cards in both slots.

Portable and compact, the ProGrade Digital CompactFlash & SD Dual-Slot reader features an industry-first magnetic base that pairs to an included metal plate. Affix the small metal plate to laptop or host device, then connect the reader to safely and efficiently transfer files—whether working in the field or studio. Two included 18" USB connector cables ensure device interoperability. Features LED indicator to show data transfer activity.

The ProGrade Digital CompactFlash & SD Dual-Slot reader is backwards compatible with USB 3.0 host devices, and supports CompactFlash and SD cards. For use with Mac™ OS X 10.6 or later and Windows™ 10 operating systems. This reader takes advantage of the latest generation USB 3.2, Gen. 2 interface, which is up to two times faster than USB 3.0.

ProGrade Digital CompactFlash & SD Dual-Slot USB 3.2, Gen. 2 Reader Key Features:

- Dual-slot reader for CompactFlash and SD cards
- Data transfer speed of up to 10Gb/s (1.25GB/s)
- Supports simultaneous maximum speed transfer of data from cards in both slots
- USB 3.2, Gen. 2 interface
- LED indicator for data transfer activity
- Portable and compact
- Includes two 18" connection cables: one Type A to Type C and one Type C to Type C
- Magnetized reader bottom connects reader to laptop (using included metal mounting plate)
- Compatible with Mac OS X 10.6 or later and Windows 10
- Backwards compatible with USB 3.0 devices
- Dimensions: 70.8 mm x 70.8 mm x 18 mm
- Storage Temperature -65°C to +150°C
- Operating Temperature 0°C to +70°C
- 2-year warranty
- Refresh Pro™ enabled to quickly refresh card performance and monitor card health

