

Memory Card Choice of Professionals

CFexpress[™] Type-B & SD[™] Dual-Slot USB 3.2, Gen. 2 Workflow Reader

USB 3.2, Gen. 2 Transfer Speed

Transfer your data files at speeds of up to 10Gb/s (1.25GB/s) using the ProGrade Digital CFexpress & SD Workflow Reader. Indispensable for cinema, video and photography workflows where large volumes of data files are the norm, this reader provides simultaneous rapid and efficient transfer of data from card.

Portable and compact, the ProGrade Digital CFexpress & SD reader features an industry-first magnetic base that pairs to an included metal plate. Affix the small metal plate to laptop or host device, then connect the reader to safely and efficiently transfer files—whether working in the field or studio. Two included 18" USB connector cables ensure device interoperability. Features LED indicator to show data transfer activity.

The ProGrade Digital CFexpress & SD reader is backwards compatible with USB 2.0/3.0/3.1 host devices and supports CFexpress & SD cards. For use with Mac™ OS X 10.6 or later and Windows™ 10 operating systems. This reader takes advantage of the latest generation USB 3.2, Gen. 2 interface, which is up to two times faster than USB 3.0.

ProGrade Digital CFexpress & SD Dual-Slot USB 3.2, Gen. 2 Reader Key Features:

- Dual-slot reader for CFexpress & SD cards
- Data transfer speed of up to 10Gb/s (1.25GB/s)
- USB 3.2, Gen. 2 interface
- LED indicator for data transfer activity
- Portable and compact
- Includes two 18" connection cables: one Type A to Type C and one Type C to Type C
- Magnetized reader bottom connects reader to laptop (using included metal mounting plate)
- Not backwards compatible with XQD cards
- Compatible with Mac OS X 10.6 or later and Windows 10
- Backwards compatible with USB 3.0 devices
- Dimensions: 70.8 mm x 70.8 mm x 18 mm
- Storage Temperature -65°C to +150°C
- Operating Temperature 0°C to +70°C
- 2-year warranty
- Refresh Pro[™] enabled to quickly refresh card performance and monitor card health

www.progradedigital.com

1GB=1,000,000,000 bytes. Actual user storage is less. Speed is based on internal testing; user's performance may be lower depending on host device, interface, usage conditions and other factors. 1MB = 1,000,000 bytes. ©2020 ProGrade Digital, Inc All rights reserved. Information, products, and/or specifications are subject to change without notice. ProGrade Digital, Inc is not responsible for omissions or errors in typography or photography. ProGrade and the ProGrade Logs are tademarks of ProGrade Digital is an authorized licensee of SDXC, CirceSDXC, CorpactFlash, and Crexpress trademarks. All other brand or product names in the release are trademarks or registered trademarks of their respective holders. See product packaging and www.progradedigital.com for additional information and limitations. ProGrade Digital memory cards and card readers are available for purchase online at ProGradeDigital.com, plus the company's Amazon and B&H Photo and Video websites. ProGrade Digital 1660 Hamilton Ave. Suite 101, San Jose, CA 95125, USA

