

### microSDXC™ Dual-Slot USB 3.2, Gen. 2 Workflow Reader

#### USB 3.2, Gen. 2 Transfer Speed

Transfer your data files at speeds of up to 10Gb/s (1.25GB/s) using the ProGrade Digital microSDXC™ Dual-Slot Workflow Reader. Indispensable for drone, action cam, video and photography workflows where large volumes of data files are the norm, this reader provides simultaneous rapid and efficient transfer of data from cards in both slots.

Portable and compact, the ProGrade Digital microSDXC Dual-Slot reader features an industry-first magnetic base that pairs to an included metal plate. Affix the small metal plate to laptop or host device, then connect the reader to safely and efficiently transfer files—whether working in the field or studio\*. Two included 18" USB connector cables ensure device interoperability. Features LED indicator to show data transfer activity.

The ProGrade Digital microSDXC Dual-Slot reader is backwards compatible with USB 3.0 host devices, and supports microSDXC cards. For use with Mac OS X 10.6+ and Windows 10+ operating systems. This reader takes advantage of the latest generation USB 3.2, Gen. 2 interface, which is up to two times faster than USB 3.0.

#### ProGrade Digital microSDXC Dual-Slot USB 3.2, Gen. 2 Reader Key Features:

- Dual-slot reader for microSDXC cards
- Data transfer speed of up to 10Gb/s (1.25GB/s)
- Supports simultaneous maximum speed transfer of data from cards in both slots
- USB 3.2, Gen. 2 interface
- LED indicator for data transfer activity
- Portable and compact
- Includes two 18" connection cables: one Type A to Type C and one Type C to Type C
- Magnetized reader bottom connects reader to laptop\* (using included metal mounting plate)
- Compatible with Mac OS X 10.6+ and Windows 10+
- Backwards compatible with USB 3.0 devices
- Dimensions: 70.8 mm x 70.8 mm x 18 mm
- Storage Temperature -65°C to +150°C
- Operating Temperature 0°C to +70°C
- 2-year warranty
- Refresh Pro™ enabled to quickly refresh card performance and monitor card health
- U.S. Patent #10,936,831

