

### CFexpress™ Type B & SD™ Dual-Slot USB 3.2, Gen. 2 Workflow Reader

#### USB 3.2, Gen. 2 Transfer Speed

Transfer your data files at speeds of up to 10Gb/s (1.25GB/s) using the ProGrade Digital CFexpress Type B & SD Workflow Reader. Indispensable for cinema, video and photography workflows where large volumes of data files are the norm, this reader provides simultaneous rapid and efficient transfer of data from card.

Portable and compact, the ProGrade Digital CFexpress Type B & SD reader features an industry-first magnetic base that pairs to an included metal plate. Affix the small metal plate to laptop\* or host device, then connect the reader to safely and efficiently transfer files—whether working in the field or studio\*. Two included 18" USB connector cables ensure device interoperability. Features LED indicator to show data transfer activity.

The ProGrade Digital CFexpress Type B & SD reader is backwards compatible with USB 2.0/3.0/3.1 host devices and supports CFexpress Type B & SD cards. For use with Mac OS X 10.6+ and Windows 10+ operating systems. This reader takes advantage of the latest generation USB 3.2, Gen. 2 interface, which is up to two times faster than USB 3.0.

#### ProGrade Digital CFexpress Type B & SD Dual-Slot USB 3.2, Gen. 2 Reader Key Features:

- Dual-slot reader for CFexpress Type B & SD cards
- Data transfer speed of up to 10Gb/s (1.25GB/s)
- USB 3.2, Gen. 2 interface
- LED indicator for data transfer activity
- Portable and compact
- Includes two 18" connection cables: one Type A to Type C and one Type C to Type C
- Magnetized reader bottom connects reader to laptop\* (using included metal mounting plate)
- Not backwards compatible with XQD cards
- Compatible with Mac OS X 10.6+ and Windows 10+
- Backwards compatible with USB 3.0 devices
- Dimensions: 70.8 mm x 70.8 mm x 18 mm
- Storage Temperature -65°C to +150°C
- Operating Temperature 0°C to +70°C
- 2-year warranty
- Refresh Pro™ enabled to quickly refresh card performance and monitor card health
- U.S. Patent #10,936,831

